

Application

Emergency Light Luminaires are designed to provide clear emergency illumination and path guidance in accordance with international standards, with a stylish design that complements any building, using high-quality materials and clear, accurate symbols.

Specification

Housing:	High-impact thermo ABS case, 1.2 mm. Electro-galvanized steel sheet
Finishing:	Epoxy powder coated and stove enamel
Input:	220 VAC $\pm 10\%$ 50 Hz 1 Phase
Output:	Lamp 220 VAC 220 VAC 50 Hz $\pm 10\%$ Pure Sine Wave
Control system:	Automatic solid state system with Microcontroller
Charging system:	Constant Current and Constant Voltage Charge
Charging duration:	12-15 Hours
Battery:	Sealed Lead Acid
Safety features:	AC Fuse - Protection of AC 220V input : DC Fuse - Protection of battery charger
Duration :	2 Hours



Model	Max Lamp Load (W)	Output Current (A)	Battery Voltage (V)	Battery Capacity (Ah)	Dimensions (cm)		
					W	L	H
TEEL-HP100	100	0.5	24	14	20.5	35	35.5
TEEL-HP200	200	0.9	24	26	25	40	55
TEEL-HP300	300	1.4	24	40	25	40	55
TEEL-HP400	400	1.9	24	55	25	40	55
TEEL-HP500	500	2.3	24	65	30	40.5	94
TEEL-HP700	700	3.2	24	90	30	40.5	94
TEEL-HP800	800	3.7	24	100	30	40.5	94
TEEL-HP900	900	4.1	24	110	35	40	90
TEEL-HP1000	1000	4.6	24	120	35	40	90
TEEL-HP1200	1200	5.5	48	75	40	45	100
TEEL-HP1300	1300	5.9	48	80	40	45	100
TEEL-HP1500	1500	6.8	48	90	40	45	100
TEEL-HP1700	1700	7.7	48	110	40	45	100
TEEL-HP2000	2000	9.1	48	130	40	45	100