


Application

Recessed Profile Mirror Louver (Gypsum) luminaires are suitable for offices, schools, hospitals, and commercial spaces where high illumination levels, energy efficiency, glare control, and uniform lighting are required.



Specification

Housing:	Die-formed cold-rolled steel sheet 0.6 mm thickness
Finishing:	Polyester powder coated
Reflector:	Mirror anodized aluminium reflector with 87% reflectance (95% optional)
Louver:	Mirror anodized aluminium louver with Christmas tree profile for glare control
Mounting:	Recessed mounting for gypsum ceiling
Lamp Holder:	G13 rotary lock types with TIS standard
Wiring:	THW 1.0 sqmm with TIS standard
Light Source:	LED T8 Lamps
IP Rating:	IP20



Model	Light Source	Dimensions (mm)				
		W1	W2	L1	L2	H
TG-12L	1 x LED T8 L 600 mm	130	150	642	630	77
TG-12LX	1 x LED T8 L 600 mm	280	294	642	630	77
TG-22L	2 x LED T8 L 600 mm	280	294	642	630	77
TG-22LX	2 x LED T8 L 600 mm	580	594	642	630	77
TG-32L	3 x LED T8 L 600 mm	580	594	642	630	77
TG-42L	4 x LED T8 L 600 mm	580	594	642	630	77
TG-14L	1 x LED T8 L 1200 mm	130	150	1242	1230	77
TG-14LX	1 x LED T8 L 1200 mm	280	294	1242	1230	77
TG-24L	2 x LED T8 L 1200 mm	280	294	1242	1230	77
TG-24LX	2 x LED T8 L 1200 mm	580	594	1242	1230	77
TG-34L	3 x LED T8 L 1200 mm	580	594	1242	1230	77
TG-44L	4 x LED T8 L 1200 mm	580	594	1242	1230	77