


Application

Surface Double Parabolic Louver luminaires are suitable for offices, schools, hospitals, and commercial spaces where high illumination levels, energy efficiency, glare control, and uniform lighting are required.



Specification

- Housing:** Die-formed cold-rolled steel sheet 0.6 mm thickness
- Finishing:** Polyester powder coated
- Reflector:** Mirror anodized aluminium reflector with 87% reflectance (95% optional)
- Louver:** Mirror anodized aluminium double parabolic louver for glare control
- Mounting:** Surface and suspension rod mounting
- Lamp Holder:** G13 rotary lock types with TIS standard
- Wiring:** THW 1.0 sqmm with TIS standard
- Light Source:** LED T8 Lamps
- IP Rating:** IP20



Model	Light Source	Dimensions (mm)		
		W	L	H
TOD-12L	1 x LED T8 L 600 mm	150	615	77
TOD-12LX	1 x LED T8 L 600 mm	300	615	77
TOD-22L	2 x LED T8 L 600 mm	300	615	77
TOD-22LX	2 x LED T8 L 600 mm	600	615	77
TOD-32L	3 x LED T8 L 600 mm	600	615	77
TOD-42L	4 x LED T8 L 600 mm	600	615	77
TOD-14L	1 x LED T8 L 1200 mm	150	1222	77
TOD-14LX	1 x LED T8 L 1200 mm	300	1222	77
TOD-24L	2 x LED T8 L 1200 mm	300	1222	77
TOD-24LX	2 x LED T8 L 1200 mm	600	1222	77
TOD-34L	3 x LED T8 L 1200 mm	600	1222	77
TOD-44L	4 x LED T8 L 1200 mm	600	1222	77