


Application

Recessed Double Parabolic Louver (Gypsum) luminaires are suitable for offices, schools, hospitals, and commercial spaces where high illumination levels, energy efficiency, glare control, and uniform lighting are required.



Specification

- Housing:** Die-formed cold-rolled steel sheet 0.6 mm thickness
- Finishing:** Polyester powder coated
- Reflector:** Mirror anodized aluminium reflector with 87% reflectance (95% optional)
- Louver:** Mirror anodized aluminium double parabolic louver for glare control
- Mounting:** Recessed mounting for gypsum ceiling
- Lamp Holder:** G13 rotary lock types with TIS standard
- Wiring:** THW 1.0 sqmm with TIS standard
- Light Source:** LED T8 Lamps
- IP Rating:** IP20



Model	Light Source	Dimensions (mm)				
		W1	W2	L1	L2	H
TGD-12L	1 x LED T8 L 600 mm	130	150	642	630	77
TGD-12LX	1 x LED T8 L 600 mm	280	294	642	630	77
TGD-22L	2 x LED T8 L 600 mm	280	294	642	630	77
TGD-22LX	2 x LED T8 L 600 mm	580	594	642	630	77
TGD-32L	3 x LED T8 L 600 mm	580	594	642	630	77
TGD-42L	4 x LED T8 L 600 mm	580	594	642	630	77
TGD-14L	1 x LED T8 L 1200 mm	130	150	1242	1230	77
TGD-14LX	1 x LED T8 L 1200 mm	280	294	1242	1230	77
TGD-24L	2 x LED T8 L 1200 mm	280	294	1242	1230	77
TGD-24LX	2 x LED T8 L 1200 mm	580	594	1242	1230	77
TGD-34L	3 x LED T8 L 1200 mm	580	594	1242	1230	77
TGD-44L	4 x LED T8 L 1200 mm	580	594	1242	1230	77