


Application

Emergency Light luminaires are designed to provide clear emergency illumination and path guidance in accordance with international standards, with a stylish design that complements any building, using high-quality materials and clear, accurate symbols.

Specification

Housing:	High-impact thermo ABS case,
Finishing:	Epoxy powder coated and stove enamel
Mounting:	Wall mount
Input:	220 VAC $\pm 10\%$ 50 Hz 1 Phase
Light Source:	2x9W & 12W SMD LED Super wide beam 90°/ Spot Beam 40°
Control system:	Automatic solid state system with Microcontroller
Charging system:	Constant Current and Constant Voltage Charge
Charging duration:	10-20 Hours
Battery:	Lithium Ferro Phosphate (LiFePo4)
Safety features:	AC Fuse - Protection of AC 220V input : DC Fuse - Protection of battery charger
Op. Temp:	10°C to 40°C
IP Rating:	IP20



Model	Battery (LiFePo4)	Power (W)	Brightness (lm)	Beam (°)	Dimensions (cm)		
					W	L	H
TEEL-CP369	3.2V 3600 mAh	2 x 9 2 x 12	845 1000	40 40	6.5	22	21.5
TEEL-CP04	3.2V 5500 mAh	2 x 9 2 x 12	845 1000	40 40	6.5	22	21.5
TEEL-CP08	3.2V 7200 mAh	2 x 9 2 x 12	845 1000	40 40	6.5	22	21.5