

Application

Emergency Light Luminaires are designed to provide clear emergency illumination and path guidance in accordance with international standards, with a stylish design that complements any building, using high-quality materials and clear, accurate symbols.

Specification

Housing:	High-impact thermo ABS case, 1.2 mm. Electro-galvanized steel sheet
Finishing:	Epoxy powder coated and stove enamel
Input:	220 VAC $\pm 10\%$ 50 Hz 1 Phase
Output:	Remote lamp 12VDC or 24 VDC
Control system:	Automatic solid state system with Microcontroller
Charging system:	Constant Current and Constant Voltage Charge
Charging duration:	12-15 Hours
Battery:	Sealed Lead Acid
Safety features:	AC Fuse - Protection of AC 220V input : DC Fuse - Protection of battery charger
Duration :	2 Hours



Model	Max Lamp Load (W)	Output Channel	Battery Voltage (V)	Battery Capacity (Ah)	Dimensions (cm)		
					W	L	H
TEEL-CU21-24	160	1	24	21	18	25	39.5
TEEL-CU26-24	220	1	24	26	18	25	39.5
TEEL-CU40-24	360	1	24	40	34	40	50
TEEL-CU65-24	600	1	24	65	40	40	50
TEEL-CU7-12	30	1	12	7	12.5	23	25
TEEL-CU18-12	80	1	12	18	12	29	35
TEEL-CU26-12	120	1	12	26	13	25	39.5
TEEL-CU40-12	180	1	12	40	13	25	39.5
TEEL-CU65-12	300	1	12	65	34	40	50
TEEL-CU100-12	450	1	12	100	34	40	50
TEEL-CU134-12	620	1	12	134	60	40	100
TEEL-CU150-12	690	1	12	150	60	40	100