


FLUORESCENT T8



INDUSTRIAL TYPE FIXTURE

APPLICATIONS

- SCHOOLS, STORES, HOMES, WORKSHOPS.
- RESIDENTS.

SPECIFICATION FEATURES

- DIE-FORMED COLD-ROLLED STEEL 0.6 MM. STEEL THICKNESS.
- FIVE-STAGES PHOSPHATE PRETREATMENT COATING TO ENSURE SUPERIOR PAINT ADHESION AND RUST RESISTANCE.
- FINISHED WITH HIGH GLOSSY, BAKED WHITE POLYESTER POWDER.
- THW 0.5 SQMM. WIRING CABLE.
- HEAVY DUTY SPRING LOCKED LAMPHOLDER AND STARTER HOLDER.

REFLECTOR

- WHITE STOVED ENAMELLED POWDER COAT.

INSTALLATION

- AVAILABLE IN SURFACE AND SUSPENSION ROD MOUNTING.

MODEL	LAMP	WIDE (W)	LONG (L)	HIGH (H)	PRICE (Baht)	COMPLETE SET
TI-12	1 x 18W.	195	620	82	260	500
TI-22	2 x 18W.	265	620	82	440	920
TI-14	1 x 36W.	195	1224	82	400	640
TI-24	2 x 36W.	285	1224	82	590	1,070